


Diverge Skinny Tile

Product Specifications

Collection Name	Right Angle	
Style Number	L0330	
Product Type	Modular	
Construction	Multi-Level Pattern Loop	
Fiber Type	Solution Q Extreme® Cationic Fiber	
Dye Method	100% Solution Dyed	
	English	Metric
Gauge	1/12	47.24 per 10 cm
Stitches Per Inch	11	43.31 per 10 cm
Tufted Pile Height	3/32" low - 6/32" high	2.38mm - 4.76mm
Tufted Yarn Weight	22.0	745.93 g/m ²
Finished Pile Thickness	0.101	2.57 mm
Product Size	18" X 36"	45.72 cm x 91.44 cm
Density	7842	14.60 kilotex
Protective Treatments	None	
Primary Backing	Non-Woven Synthetic	
Secondary Backing	EcoWorx® Tile	
GSA Approved Product	Yes	


Performance Specifications

Traffic Class	Heavy (TARR)
Antimicrobial Assessment	Passes (AATCC-174) (When installed using Shaw 5036 adhesive)
Methanamine Pill Test	Passes (DOCF-1-70)
Radiant Panel	Class I (ASTM E-648)
NBS Smoke	Less than 450 (ASTM-E-662)
Electrostatic Propensity	Less than 3.5 kV (AATCC-134)
CRI Green Label Plus	Certified GLP9968
ADA Compliance	This product meets the guidelines as set forth in the Americans with Disabilities Act for minimum static coefficient of friction of 0.6 for accessible routes.

Warranty Information

Lifetime Commercial Limited

Installation Methods



transforming performance.



Environmental Specifications

Recyclability 100% recyclable

Materials

Ingredients

Face Fiber Solution Q Extreme® Cationic Nylon 6
Dye Method 100% Solution Dyed
Backing Polyolefin Composite

does not contain PVC, phthalates, or PBD/PBDE

Recycled Content

Total Backing Recycled Content	60%
Total Fiber Recycled Content	0%
Total Recycled Content (by weight)	46%
Pre-Consumer	36%
Post-Consumer	10%
Bio-Based/Rapidly Renewable Content (By Weight)	0%
Packaging	100% Recyclable
Country of Origin (manufacturer)	USA

**Recycled Content values are shown as whole number value.*

Meets or exceeds all local and national regulations in country of manufacture.

Manufactured in an ISO9001 & ISO14001 certified facility or equivalent.

Recycled content is calculated using system allocation, mass balance, and direct insertion.

The actual recycled content in this product will likely vary. For more information email info@shawgreenedge.com.

Third Party Certifications

MBDC Cradle to Cradle	Silver Certified
NSF 140	Platinum Certified
CRI Green Label Plus	Certified GLP9968
USGBC LEED	Contributes