

Cube & Colour 12" x 48"

Product Specifications

Collection Name	Mixed Materials Converge	
Style Number	L0427	
Product Type	Modular	
Construction	Multi-Level Pattern Loop	
Fiber Type	Solution Q Extreme® Cationic Fiber	
Dye Method	100% Solution Dyed	
	English	Metric
Gauge	1/12	47.24 per 10 cm
Stitches Per Inch	10	39.37 per 10 cm
Tufted Pile Height	3/32" low - 6/32" high	2.38mm - 4.76mm
Tufted Yarn Weight	22.0	745.93 g/m ²
Finished Pile Thickness	0.097	2.46 mm
Product Size	12" x 48"	30.48 cm x 121.92 cm
Density	8165	15.20 kilotex
Protective Treatments	N/A	
Primary Backing	Non-Woven Synthetic	
Secondary Backing	EcoWorx® Tile	


Performance Specifications

Traffic Class	Heavy (TARR)
Antimicrobial Assessment	Passes (AATCC-174) (When installed using Shaw 5036 adhesive)
Methanamine Pill Test	Passes (DOCF-1-70)
Stain Resistance	Passes (AATCC-175)
Radiant Panel	Class I (ASTM E-648)
NBS Smoke	Less than 450 (ASTM-E-662)
Electrostatic Propensity	Less than 3.5 kV (AATCC-134)
CRI Green Label Plus	glp9968
ADA Compliance	This product meets the guidelines as set forth in the Americans with Disabilities Act for minimum static coefficient of friction of 0.6 for accessible routes.

Warranty Information

Lifetime Commercial Limited

Installation Methods



transforming performance.



Environmental Specifications

Recyclability 100% recyclable

Materials

Ingredients

Face Fiber	Solution Q Extreme® Cationic Nylon 6
Dye Method	100% Solution Dyed
Backing	Polyolefin Composite
Surface Treatments	non c8 fluorocarbon chemistry

does not contain PVC, phthalates, or PBD/PBDE

Recycled Content

Total Backing Recycled Content	60%
Total Fiber Recycled Content	0%
Total Recycled Content (by weight)	46%
Pre-Consumer	36%
Post-Consumer	10%
Bio-Based/Rapidly Renewable Content (By Weight)	0%
Packaging	100% Recyclable
Country of Origin (manufacturer)	USA

**Recycled Content values are shown as whole number value.*

Meets or exceeds all local and national regulations in country of manufacture.

Manufactured in an ISO9001 & ISO14001 certified facility or equivalent.

Recycled content is calculated using system allocation, mass balance, and direct insertion.

The actual recycled content in this product will likely vary. For more information email info@shawgreenedge.com.

Third Party Certifications

MBDC Cradle to Cradle	Silver Certified
NSF 140	Platinum Certified
CRI Green Label Plus	GLP 9968
USGBC LEED	Contributes
Building Research Establishment	Contributes
Good Environmental Choice Australia	Contributes
Singapore Green Label	Certified 039-003

transforming performance.

patcraft.com | 800.241.4014