

Realize

Product Specifications

Collection Name	Tangible Hue	
Style Number	L0489	
Product Type	Modular	
Construction	MULTI-LEVEL PATTERN LOOP	
Fiber Type	Solution Q Extreme® Nylon	
Dye Method	100% Solution Dyed	
	English	Metric
Gauge	1/12	47.24 per 10 cm
Stitches Per Inch	10	39.37 per 10 cm
Tufted Pile Height	5/32" low - 6/32" high	3.97mm - 4.76mm
Tufted Yarn Weight	19	644.21 g/m ²
Finished Pile Thickness	0.107	2.72 mm
Total Thickness	0.232	5.89 mm
Product Size	24" x 24"	60.96 cm x 60.96 cm
Average Density	6,393	11.90 kilotex
Installation Pattern Repeat	TILE	tile
Primary Backing	Synthetic	
Secondary Backing	EcoWorx® Tile	


Performance Specifications

Traffic Class	Heavy (TARR)
Antimicrobial Assessment	Passes (AATCC-174) (When installed using Shaw 5036 adhesive)
Methenamine Pill Test	Passes (DOCF-1-70)
Radiant Panel	Class I (ASTM E-648)
NBS Smoke	< 450 (ASTM-E-662)
Electrostatic Propensity	Less than 3.5 kV (AATCC-134)
CRI Green Label Plus	certified glp9968
ADA Compliance	This product meets the guidelines as set forth in the Americans with Disabilities Act for minimum static coefficient of friction of 0.6 for accessible routes.

Warranty Information

Lifetime Commercial Limited

Installation Methods



MERGEABLE - Allows modular products to be installed using multiple dye lots.



Environmental Specifications

Recyclability 100% recyclable

Materials

Ingredients

Face Fiber Solution Q Extreme® Cationic Nylon 6
Dye Method 100% Solution Dyed
Backing Polyolefin Composite
Surface Treatments non c8 fluorocarbon chemistry

does not contain PVC, phthalates, or PBD/PBDE

Recycled Content

Total Backing Recycled Content 62%
Total Fiber Recycled Content 0%
Total Recycled Content (by weight) 49%
Pre-Consumer 39%
Post-Consumer 10%
Bio-Based/Rapidly Renewable Content (By Weight) 0%
Packaging 100% Recyclable
Country of Origin (manufacturer) USA

**Recycled Content values are shown as whole number value*

Meets or exceeds all local and national regulations in country of manufacture.

Manufactured in an ISO9001 & ISO14001 certified facility or equivalent.

Recycled content is calculated using system allocation, mass balance, and direct insertion.

The actual recycled content in this product will likely vary. For more information email info@shawgreenedge.com.

Third Party Certifications

MBDC Cradle to Cradle	Silver Certified
NSF 140	Platinum Certified
CRI Green Label Plus	certified glp9968
USGBC LEED	contributes

Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate specification changes without notice. This carpet is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another carpet design is also strictly prohibited. Visit patcraft.com/testing for more information.

transforming performance.