


spectrum tile platinum

product type:	carpet tile	
collection:	no rules	
style number:	L9584	
construction:	multi-level pattern loop	
fiber:	solution q extreme® nylon	
dye method:	100% solution dyed	
primary backing:	synthetic	
secondary backing:	ecoworx® tile	
protective treatments:	inherent stain resistance	
warranty:	lifetime commercial limited	
	u.s.	metric
product size:	24.0 x 24.0 inches	61.0 x 61.0 cm
gauge:	1/12 inch	47.2 per 10cm
stitches:	8 per inch	33 per 10cm
finished pile thickness:	0.115 inches	2.92 mm
average density:	6261 per cu.yd.	0.232 g/cm3
kilotex:		9.30 kilotex
total thickness:	0.249 inches	6.32 mm
tufted weight:	20 oz/yd2	678.1 gms/sqm
pattern repeat:	none	none



recommended installation method



coordinating products

carpet tile: [blox tile](#), [color play tile](#), [kinetic tile](#), [captivate tile](#), [intrigue tile](#), [diffuse 24x24](#), [disperse 24x24](#), [chroma tile](#), [smp navajo ew24 tile](#)
 broadloom: [banyan tree tlk](#), [timbermill tlk](#)

performance + testing

antimicrobial assessment:	passes (AATCC-174) (When installed using Shaw 5036 adhesive)
pill test:	pass
radiant panel:	class I
nbs smoke:	less than 450
electrostatic propensity:	less than 3.5 kv
CRI greenlabel plus:	USA (GLP9968)
ADA compliance:	This product meets the guidelines as set forth in the Americans with Disabilities Act for minimum static coefficient of friction of 0.6 for accessible routes.

